

## Day/Night Vandal Proof Camera NVC-BDN4402V



### Features

- Mechanical IR cut filter
- IR operation capability
- Horizontal resolution: up to 650 TVL
- Min. Illumination: from 0.01 lx/F=1.2
- Digital Noise Reduction (DNR)
- Auto iris DC lens: f=2.8 ~ 10.5 mm
- 3-axis camera module adjustment
- Privacy zones: 4
- Other functions: mirror picture effect, motion detection
- Full configuration directly from the camera (user friendly OSD)
- IP 65
- Vandal proof housing
- Power supply: 12 VDC

Specifications	Description
Pick-up Element	1/3" SONY Super HAD II CCD imager
Horizontal Resolution	600 TVL - color mode, 650 TVL - B/W mode
Min. Illumination	0.1 lx/F=1.2 - color mode (1/50 s), 0.01 lx/F=1.2 - B/W mode (1/50 s)
S/N Ratio	More than 50 dB (AGC Off)
Electronic Shutter	Auto (AES): 1/50 s ~ 1/120 000 s
Auto Gain Control (AGC)	On/Off
White Balance	3 modes: Manual/ATW/AWB
Back Light Compensation (BLC)	On/Off
Synchronization	Internal
Day/Night Switching	Auto/Manual
Filter Delay	1 ~ 15 s
Lens Type	Auto iris DC: f=2.8 ~ 10.5 mm
Angle of View (H)	81° ~ 26°
Flickerless function	On/Off
Video Output	1.0 Vp-p/75 Ohm (BNC)
Set-up	On Screen Display (OSD)
Privacy Zones	4
Other Functions	Digital Noise Reduction (DNR) Motion detection, Mirror picture effect, Image sharpness adjustment
Enclosure	Vandal proof, coated aluminium, impact resistant poly-carbonate bubble
Degree of Protection	IP 65
Power Supply	12 VDC
Power Consumption	2.2 W

Specifications	Description
Operating Temperature	-10°C ~ 45°C
Dimensions (mm)	142 (Ø) x 100 (H)
Weight	863 g